



Home detectors

DAH9V - DAGB - CAVG



DAH9V SMOKE HOME DETECTOR	
Autonomous smoke detector for fire detection, with acoustic alarm	
Smoke sensibility	0,08 ~ 0,15dB / m
Temperature sensibility	57°C (model with temperature sensor)
Current in standby	8µA
Current in alarm	15mA
Temperature	0°C to 50°C
Humidity	0 a 95%RH
Acoustic alarm level	85db / 3m
Dimensions	Ø105 x 30mm
Installation requirements	
<ul style="list-style-type: none">• Centre of roof (do not install less than 10cm from the walls)	
Minimum installation recommended	
<ul style="list-style-type: none">• At least 2 detectors by house• At least 1 detector by floor	
Installation zones recommended	
<ul style="list-style-type: none">• Separator hallway outside the open bedrooms• Bedrooms normally closed• On the roof before a stair• Living room, dinner room, attic, etc.	

DAGB HOME GAS DETECTOR	
Autonomous gas detector with acoustic alarm, capable of activate a gas shut off to avoid	
Supply	220V AC
Test button	Yes
Indication LED	Yes
Acoustic level	80dB
Working temperature	-10°C ~ +50°C
Dimensions	120x100x60mm
Standard	CE
Gas type detected	1. Liquefied gas 2. Natural gas

CAVG GAS SHUT OFF ACTUATOR	
Electromechanical valve for automatic shut off of the gas supply	
Dimensions	100 x 90 x 70mm
Nominal voltage	12Vdc
Operating voltage	8Vdc - 16Vdc
Operating power	0,24W - 4,5W - 10W
Consumption	20mA - 350mA - 1000mA
Torque	10 - 30 - 40Kg / cm
Temperature	-20°C ~ +50°C
Humidity	< 95%RH