



CBF4

FIRE HOSE CABINET

Equipped fire hose cabinet Ø25 and 20m hose

Fire hose cabinet Ø25 mm according to EN 671-1 and 20 m hose length manufactured according to EN 694:2001.

It is composed by:

Vertical cabinet made of 1 mm thickness steel, painted red RAL 3000, measures 750 x 500 x 245 mm, and easy-open lock, provided with pre-holes for water supply, including reel, hose,

nozzle, swing arm, seat valve, manometer and supply hose.

It can be made in another colour, with the RAL provided by the customer, or in stainless steel, and it can be mounted in a floor bow

The fire hose cabinet can be made with blind door (CBF4PC), stainless steel blind door (CBF4PCI) and semi-blind door (CBF4PS)..

FEATURES

- Reel of Ø450 disks, painted in red RAL 3000.
- Semi-rigid hose Ø25 mm and 20 m length, manufactured according to EN 694:2001 standard.
- Nozzle Variomatic Ø25 of three positions; close, spray and jet, made of red plastic.
- Seat valve at 110° of 1", with ¼" manometer outlet.
- Non-return valve for manometer of ¼".
- Manometer graduated from 0 to 16 bars.
- Supply trigger between valve and reeling frame, with a Ø25 mm semi-rigid hose.

