

EYEHOMELIFE
EYEHOME

EYEHOMELIFE CO

EYEHOMELife

DOMESTIC DETECTION RANGE

Stand alone smoke and CO detectors for home use

The EYEHOMELife and EYEHOME detector is a photodetector that uses one of the most advanced optical detection cameras. It is designed to provide home fire protection without wiring and is easy to install.

The detector's red indicator light is easily visible. It flashes once every minute to indicate that the detector is in a surveillance state. When a fire alarm occurs, the indicator light will remain on continuously, the buzzer will sound for a long period of time and the alarm information will be sent via Wi-fi to the cloud (EYEHOMELife), and from here to the APP until it is deactivated.

The EYEHOMELifeCO gas detector is designed to provide protection in open areas without wiring, and is easy to install and mount.

The design and colour make it ideal for use in the home and small commercial premises. It is designed to detect carbon monoxide leaks.

The unit is designed for battery-powered applications. It is equipped with a robust metal mounting bracket for quick, easy and secure installation.

FEATURES

EYEHOMELIFE

- Surface mounted
- Sound warning
- LED indicator
- Wireless connection (easy to install)
- Automatic low battery warning
- Compatible with the latest versions of EN-14604 standards
- Wi-Fi connection (EYEHOMELife)

EYEHOMELIFE CO

- Detects carbon monoxide.
- Easy to install, mounting bracket included.
- LCD display.
- 85 dB audible alarm and LED warning light.
- Low battery detection.
- High quality, durable sensor.
- Self-diagnosis function by intelligent MCU software.
- Excellent reliability and high stability.
- Ideal for all kitchens.
- EN50291-1:2018 approval (TUV Certificate ID:111252250).

| TECHNICAL FEATURES | EYEHOMELIFE | EYEHOME |
|-----------------------|--|---|
| Power supply | 9VDC (with battery 6F22/6LR1) | 9VDC (with battery 6F22) |
| Operating current | standby $\leq 8\mu\text{A}$ /alarm $\leq 400\text{mA}$ | standby $\leq 8\mu\text{A}$ /alarm $\leq 20\text{mA}$ |
| Operating temperature | $-10^{\circ}\text{C} \sim 55^{\circ}\text{C}$ | |
| Humidity | $\leq 95\% \text{ HR (without condensation)}$ | |
| Wi-fi | 2.4GHZ | Sin Wi-fi |
| Sensibility | 0.18 at 0.26dBm | |
| Sound level | $\geq 85\text{dB @ 3m}$ and $\geq 93\text{dB @ 1m}$ | |
| Material | white ABS | |
| Dimensions | $\varnothing 105 \times 43\text{mm}$ | |
| Weight | 130g | |
| Standard | EN 14604:2005+2005/AC:2008 | |

| EYEHOMELIFE CO TECHNICAL FEATURES | |
|-----------------------------------|---|
| Operating voltage | 3VDC |
| Operating current | standby $< 15\mu\text{A}$ |
| | alarm $\leq 40\text{mA}$ |
| Operating temperature | $-10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ |
| Alarm | 85dB a 3m |
| Humidity | $\leq 95\% \text{ RH}$ |
| Dimensions | 104x104x39,2mm |