

SPB25

FIRE HOSE CABINET

Support for reel and fire extinguisher

Fire hose cabinet Ø25 mm according to UNE/EN 671-1 and 20 m semi-rigid hose made according UNE 694. It is composed by:

Support foot built in 1 mm thick steel sheet, painted in RAL 3000 red colour, measures 460 x 1530x 220 mm.


Provided with fixing of fire hose and extinguisher mounting bracket, input supply, hose, nozzle, seat valve, manometer and supply hose.

It can be made in another colour, with the RAL provided by the costumer.

FEATURES

- Reel of Ø460 mm disks, painted in red, with axial supply.
- Semi-rigid hose Ø25 mm and 20 m length, manufactured according to EN 694 standard and CE mark.
- Rail for hose allows the exit of the hose in any direction from the frontal 180°.
- Hose nozzle of three positions: close, spray and jet, connected to the end of the hose by threaded prop.
- Seat valve at 90° of 1", with 1/4" manometer outlet.

- Manometer graduated from 0 to 25 bars.
- Supply trigger between valve and reeling frame, with a Ø25 mm semi-rigid hose.





Compositor Wagner, 8

P.I Can Jardí 08191 Rubí

Barcelona

(+34) 935 862 690 cofem@cofem.com www.cofem.com